

FERROTECH


The Galvanized Steel Spacer



ROLLTECH

FERROTECH

The Galvanized Steel Spacer



Standard wall thickness 0.38 mm

In Cavity 12, 15 and 16
also available in 0.30 mm

The universal steel spacer called FERROTECH is suitable for use with corner keys and for bending on all known bending machines. This spacer fulfils all requirements for the manufacturing of fire prevention glass and is of significant benefit to the stability, especially if it comes to larger frames.

In comparison to aluminium the FERROTECH spacers have to be emphasized of their better thermal conductivity and less expansion. Corner keys and straight connectors can be delivered ex stock. On request the FERROTECH spacers can be delivered pre-assembled with straight connectors. Painting on the visible surface in all RAL- and NCS colours is possible on request.

Packaging (metre per unit) Length 6.000 mm	Cavity	B in mm	H in mm	Stillage (container)	Carton
	6	5.5	6.5	18.000	1.500
	8	7.5	6.5	15.000	1.260
	9	8.5	6.5	13.200	1.080
	10	9.5	6.5	12.672	960
	12	11.5	6.5	10.368	768
	14	13.5	6.5	9.216	672
	15	14.5	6.5	8.448	576
	16	15.5	6.5	8.064	576
	18	17.5	6.5	6.912	480
	20	19.5	6.5	6.144	480
	22	21.5	6.5	5.760	384
	24	23.5	6.5	5.376	384